MADE IN THE USA

00/7400XL



---Ken Ervin, Flooring Services Ltd., Farmer's Branch, TX



Dual V-track & Bearing



Frame Designed to **Integrate Automated Stops**



Scoring System

Welcome to cutting at the highest production and accuracy level. If continuous sawing and

tight tolerance is required for your operation, these units will deliver. Every component of this saw represents quality and performance. Showcasing 3 Hp. 3~ heavy duty induction motors.

heavy extruded beams with precise dual-vee bearings, and the sturdiest frame on the market, these powerhouse machines will deliver cutting accuracies to 0.005" guaranteed. Add knife scoring to eliminate all chipping on panels.

STANDARD EQUIPMENT

- 3 Hp, 3~ continuous duty induction saw motor.
- Welded steel frame and integrated stand system.
- Dual V-track precision guide system.
- Adjustable vertical and horizontal rulers.
- Quick stop gauges (8' left, 5'
 Wheels. right).
- Saw blade.

OPTIONAL EQUIPMENT

- Stop bar.
- Dust vacuum (1 Hp or 21/4 Hp). 2 Hp, 1 phase motor.
- High quality saw blades.

- Quick change from vertical to horizontal cutting.
- Floating pressure saw foot.
- Solid aluminum material rollers.
- Enclosed counterweight system.
- MID-WAY FENCETM.
- Dust collection ready.
- Hold down bar.
- 3 year warranty.
- TUV certified to UL/CSA standards.
- Material scoring attachment.
- Digital readout for vertical cuts.
 SAWGEAR™ or TigerStop® auto length measuring.

SPECIFICATIONS	计计划	
Max. Crosscut	64"	1625mm
Max. Rip Cut	Unlimited	
Max. Cut Thickness	2 ¹ / ₈ "/55mm	
Cut Accuracy, Straight and Square	0.005"/.13mm	
Blade Diameter	8"/210mm	
Motor: Standard Optional	3~230V, 7.6 amp 1~220V, 11 amp	
Frame Length: 7400 7400XL		050mm 950mm
Shipping Weight: 7400 7400XL	1097 lbs/498 kg 1228 lbs/557 kg	